

VZ MB

Liquid retarder

	Availability	
	Quantity per pallet	240
	Size / Quantity	**10 x 1 l**
	Type of container	Carton
	Container code	01
	Art. no.	
	3005	■

Application rate

Max. 1.0% for MB 2K based on total quantity
Max. 1.0% for MB TX 2K based on total quantity
Max. 0.5% for Betofix OS 5b+ based on total quantity

Range of use

- Delaying the setting rate

Property profile

- Retarding and liquefying effect

Characteristic data of the product


Density (20 °C)	Approx. 1.02 g/cm³
Consistency	Fluid
Appearance	Clear liquid

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Possible system products

- **MB 2K (3014)**
- **MB TX 2K (3004)**
- **Betofix OS 5b+ (1113)**

Directions



- **Conditions for use**


Temperature of the material, air and substrate: from min. +5 °C to max. +30 °C.

Add to the liquid component while stirring gently.
Max. quantity to be added: 250 ml per 25 kg container of MB 2K
Maximum amount to be added: 250 ml per 25 kg container MB TX 2K
Max. quantity to be added: 125 ml per 25 kg container of Betofix OS 5b+
Retarding effect at 30 °C up to 100 min.

Notes

Current regulations and legal requirements must be taken into account and deviations from these must be agreed separately.
The relevant test certificates must be observed when planning and carrying out work.

Storage / Shelf life



If stored in unopened original container in a cool, dry place, protected from frost, the product will keep for at least 9 months.

Safety data / Regulations	For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.
Disposal	Larger product residues must be disposed of in the original packaging in accordance with the applicable regulations. Do not pour liquid coating or residues down the drain, even when cleaning tools. Must not be disposed of with household waste. Completely empty packaging must be recycled.
Biocidal Products Regulation	Contains as "treated goods" a biocidal product (in-can preservative) with the biocidal active agent(s) 1,2-benzisothiazol-3(2H)-one and 2-methyl-2H-isothiazol-3-one to protect the container contents from spoilage due to microbial organisms (bacteria, yeast etc.). Always follow the directions carefully!

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never be binding, even though it is provided to the best of our knowledge In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.